

ZW5-Series, Electric Driven Workholding Pumps



- Enerpac electric driven workholding pumps can be customized to your needs
- Various models including electric controls and isolating valves
- Stackable to 8 VP-series valve stations high
- Adjustable relief valve
- Glycerine dampened pressure gauge G-2517L on pumps with VP-series valves
- 230/400 Volt - 50Hz - 1,1 kW motor, IP54 class protection
- Single stage pump; oil flow 1,64 l/min at 350 bar
- Pressure range 100 -350 bar
- 50 % continuous operation at 350 bar

Chart (Metric)

For use with cylinders		Motor	Usable Oil Capacity **	Control Valves included	Isolating Valves *** included	Electric Switch-box included	Valve-Manifold Type		Pump Model Number	Weight
S/A	D/A	Volt *	litres				VP-series	CETOP03		kg
–	–	230	10,0	–	–	–	•	–	ZW5VPSEE100	65
–	–	400	10,0	–	–	–	•	–	ZW5VPSWE100	65
–	–	230	10,0	–	–	–	–	•	ZW5C03SEE100	65
–	–	400	10,0	–	–	–	–	•	ZW5C03SWE100	65
2x	–	230	10,0	1x VP-41	–	•	•	–	ZW5141SEE100	77
2x	–	400	10,0	1x VP-41	–	•	•	–	ZW5141SWE100	77
–	1x	230	10,0	1x VP-11	•	•	•	–	ZW5111SEE100	77
–	1x	400	10,0	1x VP-11	•	•	•	–	ZW5111SWE100	77
–	2x	230	10,0	2x VP-11	•	•	•	–	ZW5211SEE100	80
–	2x	400	10,0	2x VP-11	•	•	•	–	ZW5211SWE100	80

* 230 Volt @ 3,3 Amps, 50 Hz or 400 Volt @ 1,9 Amps, 50 Hz.

** 10 litres is standard reservoir size. 4, 8, 20 or 40 litres reservoir is optional.

*** Isolating valve is PSCK-8 pressure switch.